

EDULE

SYMBOLS	DESCRIPTION	MOUNTING HEIGHT TO CENTER OF DEVICE UNLESS INDICATED	SYMBOLS	DESCRIPTION	MOUNTING HEIGHT TO CENTER OF DEVICE UNLESS INDICATED
A-0	CEILING SURFACE MOUNTED LIGHT FIXTURE. CAPITAL LETTER INDICATES FIXTURE TYPE. SMALL LETTER INDICATES SWITCHING.			VARIABLE FREQUENCY DOME BY DIVISION 15	48 INCHES
A-1	RECESSED CEILING MOUNTED LIGHT FIXTURE.			THERMAL SWITCH (MOTOR OVERLOAD TYPE)	48 INCHES
A-2	CONNECTED TO EMERGENCY LIFE SAFETY POWER.		A-E	THERMOSTAT - PROVIDE BY DIVISION 16	48 INCHES
A-3	WALL MOUNTED HORN. ON AUTO LIGHT FIXTURE.			THERMOSTAT - FURNISHED BY DIVISION 15, INSTALLED BY DIVISION 16	48 INCHES
A-4	CEILING-MOUNTED JUNCTION BOX ("C" INDICATES EMERGENCY CRITICAL BRANCH POWER; "T" INDICATES EMERGENCY LIFE SAFETY POWER; "E" INDICATES EMERGENCY EQUIPMENT POWER).	18 INCHES		HASH MARKS INDICATE ITEM NOTED TO BE REMOVED	
A-5	WALL JUNCTION BOX.			SPEAKER	80 INCHES
A-6	CEILING EXIT SIGN. SHARED SIDE INDICATES LIGHTED			WALL MOUNTED SPEAKER	80 INCHES
A-7	FACED ARROWS INSTALLED AS SHOWN.			CLOCK	78 INCHES
A-8	WALL EXIT SIGN.	6 INCHES ABOVE TOP OF WINDOW TO BOTTOM		MICROPHONE OUTLET	18 INCHES
A-9	SUSPENDED FIXTURE.			VOLUME CONTROL	48 INCHES
A-10	SURFACE FLUORESCENT.			SECURITY DEVICES: REQUEST TO EXIT	
A-11	RECESSED FLUORESCENT.			DOOR POSITION SWITCH, RECESSED	
A-12	FIXTURE CONNECTED TO EMERGENCY LIFE SAFETY POWER.			DOOR POSITION SWITCH, SURFACE MOUNT	
A-13	FIXTURE CONNECTED TO EMERGENCY CRITICAL BRANCH POWER.			CARD READER	48 INCHES
A-14	DASHED LINES INDICATE EXISTING FIXTURES, DEVICES, OR EQUIPMENT.			CAMERA	
A-15	EMERGENCY BATTERY LIGHT.	7 FOOT 6 INCHES		CEILING MOUNTED MOTION SENSOR SWITCH	48 INCHES
A-16	EMERGENCY REMOTE LAMP.			WALL MOUNTED SMALL AREA MOTION SENSOR SWITCH	48 INCHES
A-17	SWITCH. SINGLE POLE (HOUSEPOWER RATED WHEN USED AS MOTOR DISCONNECT).	48 INCHES		WALL MOUNTED LARGE AREA MOTION SENSOR SWITCH	64 INCHES
A-18	DOUBLE POLE.	48 INCHES		MOTION SENSOR SWITCH POWER PACK	
A-19	3-WAY.	48 INCHES		AUXILIARY INPUT OUTLET	18 INCHES
A-20	4-WAY.	48 INCHES		COMPUTER OUTLET (NUMBER INDICATES QUANTITY OF CABLES AND JACKS, NO NUMBER INDICATES ONE)	18 INCHES
A-21	KEY OPERATED.	48 INCHES		COMBINATION COMPUTER/TELEPHONE OUTLET IN SINGLE GANG (PENDING APPROVAL BY DIVISION 15)	18 INCHES
A-22	WITH PILOT LIGHT (CAN BE USED WITH OTHER SWITCH TYPES).	48 INCHES		TELEPHONE OUTLET ("W" INDICATES WALL MOUNTED AT 48 INCHES)	18 INCHES
A-23	FLUORESCENT DIMMER.	48 INCHES		DATA PATCH PANEL.	
A-24	MOMENTARY CONTACT.	48 INCHES		COMPUTER/TELEPHONE OUTLET. PROVIDE ROUND-IN AND CONDUIT ONLY.	18 INCHES
A-25	DIMMER (GND. WHT. UNLESS OTHERWISE NOTED).	48 INCHES		TELEVISION OUTLET	18 INCHES
A-26	LOW VOLTAGE SELECTOR.	48 INCHES		INTERCOM OUTLET	18 INCHES
A-27	LOW VOLTAGE SWITCH.	48 INCHES		INTERCOM MASTER	
A-28	2WGS GROUND BAR.			INTERCOM STAFF STATION	
A-29	DUPLEX RECEPTACLE ("C" INDICATES EMERGENCY CRITICAL BRANCH POWER).	18 INCHES		BULLZER	
A-30	DOUBLE DUPLEX RECEPTACLE ("C" INDICATES EMERGENCY CRITICAL BRANCH POWER).	18 INCHES		PUSH BUTTON	
A-31	SPECIAL PURPOSE RECEPTACLE LETTER INDICATES TYPE. SEE SPECIFICATION.	18 INCHES		KEY OPERATED POWER DISCONNECT WALL SWITCH	48 INCHES
A-32	MULTI-OUTLET ASSEMBLY - M.O.A., PROVIDE DEVICES AS SHOWN ON PLANS.			BELL	
A-33	DUPLEX RECEPTACLE, HALF SWITCHED.	18 INCHES		CONTRACTOR (NUMBER INDICATES NUMBER OF POLES)	
A-34	FLOOR OUTLET, ADDITIONAL SYMBOL INDICATES TYPE.			WEATHERPROOF	
A-35	TIME SWITCH.			ABOVE COUNTER	
A-36	PHOTO CELL.			ELECTRIC WATER COOLER	
A-37	TRANSFORMER.			NURSES CALL : CORRIDOR CALL OR ZONE LIGHT	
A-38	UNDER FLOOR DUCT.	48 INCHES		MASTER STATION	
A-39	FIRE ALARM: MANUAL STATION.			PATIENT EMERGENCY STATION	48 INCHES
A-40	RATE OF RISE DETECTOR.			SINGLE BED PATIENT STATION	
A-41	FIXED TEMPERATURE DETECTOR.			STAFF STATION	48 INCHES
A-42	DUCT PHOTOELECTRIC DETECTOR.			DUTY STATION	48 INCHES
A-43	PHOTOELECTRIC DETECTOR. ("S" INDICATES STEERING ROOM WITH AUX. CONTACT; "V" INDICATES VAN GUARD; "T" INDICATES FOR ELEVATOR RECALL).			DOUBLE BED PATIENT STATION	
A-44	COMBINATION FIRE/SMOKE DIMMER OR SMOKE DIMMER BY DIVISION 15.			EMERGENCY (CODE BLUE)	
A-45	HORN ("S" INDICATES WITH STROBE LIGHT)			NURSE LOCATION	
A-46	SPEAKER HORN ("S" INDICATES WITH STROBE LIGHT)			STAFF ASSIST	48 INCHES
A-47	CHIME ("S" INDICATES WITH STROBE LIGHT)			STAFF REGISTER	
A-48	FIRE ALARM MODULE/RELAY.			EMERGENCY PUSH BUTTON	
A-49	STROBE LIGHT.			UNIT INTERFACE	
A-50	MAGNETIC DOOR HOLD OPEN.			TELEMETRY ANTENNA	
A-51	INTERGRAL MAGNETIC DOOR CLOSER.			CONDUIT CONCEALED IN FLOOR	
A-52	TYPE OF FIRE ALARM INDICATES NUMBER OF DEVICES AT THIS LOCATION.			HOSE RUN TO PANELBOARD. QUANTITY OF CONDUITORS REQUIRED NOT INDICATED. APPROPRIATE OR NUMBER OF HOSE RUNS SHOWN. #10 INDICATES WIRE SIZE.	
A-53	FIRE ALARM CONTROL PANEL.			SURFACE CONDUIT OR SURFACE RACEWAY	
A-54	FIRE ALARM EXTENSION CABINET.			NOTE IDENTIFICATION	
A-55	FIRE ALARM NOTIFICATION APPLIANCE. CIRCUIT CABINET.			WIRE BASKET TYPE CABLE TRAY	
A-56	LIGHTING AND APPLIANCE PANELBOARD.			COMMUNICATIONS CABLE SUPPORT HANGER	
A-57	SWITCHBOARD OR MOTOR CONTROL CENTER AS NOTED.			MOLDED CASE CIRCUIT BREAKER	
A-58	ELEVATOR CONTROL CABINET BY DIVISION 14.				
A-59	SPECIAL EQUIPMENT CABINET AS NOTED.				
A-60	POWER POLE.				
A-61	MOTOR (NUMBER REFERS TO MOTOR AND EQUIPMENT SCHEDULE DISCONNECT ("T" INDICATES TIGED WHEN SHOWN).				
A-62	MAGNETIC STARTER.				
A-63	COMBINATION STARTER-DISCONNECT.				
A-64	ENCLOSED MOLDED CASE CIRCUIT BREAKER 30A/20A/10A (WALL RECESSED).				

NOTES:

1. FOR DEVICES SHOWN AS 48 INCHES MOUNTING HEIGHT, WHEN INSTALLED IN MASONRY BLOCK WALLS, MOUNTING AT 48 INCHES TO THE TOP OF THE OUTLET BOX IS ACCEPTABLE.

LUMINAIRE SCHEDULE											
TYPE	MANUFACTURERS	CATALOG INFORMATION	LAMP NO.	DATA TYPE	BALLAST NO.	DATA TYPE	INPUT WATTS	VOLTAGE	MOUNTING	FIGURE DESCRIPTION	REMARKS
A	LITHONIA OR EQUAL	SP SERIES	3	F2878	1	HIGH EFFICIENCY ELECTRONIC	72	MOULT	RECESSED LAY-IN	2'x4' STATIC LAY-IN FLUORESCENT TROFFER, RECESSED WHITE ALUM. DOOR, SPRING LOAD LATCHES, .125 INCH ACRYLIC PRISMATIC LENS.	PROVIDE INTEGRAL BALLAST DISCONNECT (FACTORY INSTALLED) FOR EACH BALLAST.
A1	EXISTING FIXTURE SALVAGED FROM DEMOLITION	SP SERIES									
A1	EXISTING FIXTURE SALVAGED FROM DEMOLITION	SP SERIES	3	F2878	1	ELECTRONIC	78	120	RECESSED LAY-IN	2'x4' STATIC LAY-IN FLUORESCENT TROFFER, RECESSED WHITE ALUM. DOOR, SPRING LOAD LATCHES, .125 INCH ACRYLIC PRISMATIC LENS.	ACCEPTABLY CLEAN FIXTURE, RE-LAMP AND REMOUNT IN NEW CEILING GRID.
B	LITHONIA OR EQUAL	2PM3N SERIES	3	F2878	1	HIGH EFFICIENCY ELECTRONIC	72	MOULT	RECESSED LAY-IN	2'x4' LAY-IN STATIC FLUORESCENT PARABOLIC LUMINAIRE, 3" PARABOLIC LOUVER FINISH, 18 CELL, DOOR TO HAVE BLACK REVEAL.	PROVIDE INTEGRAL BALLAST DISCONNECT (FACTORY INSTALLED) FOR EACH BALLAST.
B1	EXISTING FIXTURE SALVAGED FROM DEMOLITION	2PM3N SERIES									
B1	EXISTING FIXTURE SALVAGED FROM DEMOLITION	2PM3N SERIES	3	F2878	1	ELECTRONIC	78	120	RECESSED LAY-IN	2'x4' LAY-IN STATIC FLUORESCENT PARABOLIC LUMINAIRE, 3" PARABOLIC LOUVER FINISH, 18 CELL, DOOR TO HAVE BLACK REVEAL.	ACCEPTABLY CLEAN FIXTURE, RE-LAMP AND REMOUNT IN NEW CEILING GRID.
C	LITHONIA OR EQUAL	2PM3N SERIES	3	F1778	1	HIGH EFFICIENCY ELECTRONIC	44	MOULT	RECESSED LAY-IN	2'x2' LAY-IN STATIC FLUORESCENT PARABOLIC LUMINAIRE, 3" PARABOLIC LOUVER WITH SEMI-SPECULAR LOUVER FINISH, 9 CELL, DOOR TO HAVE BLACK REVEAL.	PROVIDE INTEGRAL BALLAST DISCONNECT (FACTORY INSTALLED) FOR EACH BALLAST.
C1	EXISTING FIXTURE SALVAGED FROM DEMOLITION	2PM3N SERIES									
C1	EXISTING FIXTURE SALVAGED FROM DEMOLITION	2PM3N SERIES	3	F1778	1	ELECTRONIC	46	120	RECESSED LAY-IN	2'x2' LAY-IN STATIC FLUORESCENT PARABOLIC LUMINAIRE, 3" PARABOLIC LOUVER WITH SEMI-SPECULAR LOUVER FINISH, 9 CELL, DOOR TO HAVE BLACK REVEAL.	ACCEPTABLY CLEAN FIXTURE, RE-LAMP AND REMOUNT IN NEW CEILING GRID.
D	ALCO OR APPROVED	BU3000 SERIES	2	F1778	1	HIGH EFFICIENCY ELECTRONIC	29	MOULT	WALL SURFACE	2 FOOT OVER MIRROR FLUORESCENT BULLET NOSE WALL BRACKET, WHITE FINISH, DOWN LIGHT ONLY, PRISMATIC LENS, MOUNT 3 INCHES ABOVE MIRROR.	PROVIDE INTEGRAL BALLAST DISCONNECT (FACTORY INSTALLED) FOR EACH BALLAST.
	OMEGA OR EQUAL, BY PRE-COULTE, RUBBELL, PORTFOLIO, INFINITI, LORTOLDER	OM61-H1391T-SRO-SWR-MOULT	1	CF-321RT	1	ELECTRONIC	36	MOULT	CEILING RECESSED	SHALLOW RECESSED SHOWER LIGHT, 6 INCH APERTURE, STRIPLED CLEAR POLYCARBONATE LENS, WHITE POLYCARBONATE TRIM RING, UL LISTED FOR WET LOCATION.	

1. LUMINAIRE TYPES DEFINED WITH A MANUFACTURER'S SERIES FOLLOWED BY A LETTER OR LETTERS INDICATING THE TYPE OF LUMINAIRE. FOR TOTAL, DO NOT REQUIRE PRIOR APPROVAL FOR SUBSTITUTED PRODUCT FROM METAL OR EXCEEDING THE QUALITIES AND STANDARDS SET FORTH OF THE LISTED MANUFACTURER AND SERIES.

2. LUMINAIRE TYPES DEFINED WITH A MANUFACTURER'S SERIES FOLLOWED BY "OR APPROVED SUBSTITUTION" DOES REQUIRE PRIOR APPROVAL FOR THE SUBSTITUTED PRODUCT FOR EXCEEDING THE QUALITIES AND STANDARDS SET FORTH OF THE LISTED MANUFACTURER AND SERIES.

3. COLOR TEMPERATURE FOR ALL LAMPS ON THIS PROJECT IS 4100K UNLESS OTHERWISE SPECIFIED.

[illegible]